

# Feather Removal Machine FRM-3

The economic and mechanical way of removing poultry feathers.



## Features and benefits

- Increased the number of birds processed per day
- Compact gearbox
- Less energy consumption
- Remove feathers without any major damage to the chicken
- Stainless Steel body
- Easy to use and maintain

## Description

The de-feathering machine is developed for removing the feathers from several types of poultry, the machine is equipped with "Silicon fingers" specifically designed to beat off the feathers.

- Motor gearbox drive a high power from the motor with compact size
- The silicon fingers are a long life, more dress rate than other brand and finest quality Ultra-soft Plucking
- Made from stainless steel structure and body cover the food grade requirements.
- The plastic basket collecting feather makes it easy in management and filters the feathers from washing water.

## Specifications

- Loading capacity 3KG
- Working capacity 250 birds/hour (Estimated at 1KG bird weight)

### Dimensions

- Overall height 0.815 m
- Overall width 0.60 m
- Overall depth 0.865 m (Note: all dimensions subject to change without notice)

### Body and construction

- Stainless steel 304.

### Connections

- Power 700 Watt, 0.5HP
- Voltage 230 V / 50 Hz (earth required)
- Water supply 1/2" hose
- Water drainage 1 1/2" with ball valve shut-off

All photographs, measurements, and descriptions are provided without engagement. We reserve the right to make modifications at any time

Adham Farm Equipment Manufacturing

T +971 4 258 2125 - F +971 4 258 2124

[info@adhamfarm.com](mailto:info@adhamfarm.com) - [www.adhamfarm.net](http://www.adhamfarm.net)